### C9200L-24P-4X-E Datasheet

Check its price: Click Here



### Overview

C9200L-24P-4X-E is the Catalyst 9200L 24 ports full PoE+ 4x10G uplink Switch, with Network Essentials software. Cisco® Catalyst® 9200 Series switches extend the power of intent-based networking and Catalyst 9000 hardware and software innovation to a broader set of deployments. With its family pedigree, Catalyst 9200 Series switches offer simplicity without compromise – it is secure, always on, and IT simplified.

#### **Quick Spec**

#### Table 1 shows the quick spec.

| Model  | C9200L-24P-4X-E                               |
|--|---|
| Downlinks total 10/100/1000 or PoE+ copper ports | 24 ports full PoE+                            |
| Uplink configuration                             | 4x 10G fixed uplinks                          |
| Default primary AC power supply                  | PWR-C5-600WAC                                 |
| Fans   | Fixed redundant                               |
| Software   | Network Advantage                             |
| Stacking bandwidth                               | 80 Gbps                                       |
| DRAM   | 2 GB  |
| Flash  | 4 GB  |
| Switching capacity                               | 128 Gbps                                      |
| Forwarding rate                                  | 190.4 Mpps                                    |
| Chassis Dimensions                               | 1.73 x 17.5 x 11.3 in<br>4.4 x 44.5 x 28.8 cm |

#### **Product Details**

#### Catalyst 9200 series provides these highlights:

- Up to 48 ports of full Power over Ethernet Plus (PoE+) capability
- Resiliency with Field-Replaceable Units (FRU) and redundant power supply, fans, and modular uplinks
- Flexible downlink options with data or PoE+
- Operational efficiency with optional backplane stacking, supporting stacking bandwidth up to 160 Gbps
- UADP 2.0 Mini with integrated CPU offers customers optimized scale with better cost structure
- Enhanced security with AES-128 MACsec encryption, policy-based segmentation, and trustworthy systems
- Layer 3 capabilities, including OSPF, EIGRP, ISIS, RIP, and routed access
- Advanced network monitoring using Full Flexible NetFlow
- Cisco Software-Defined Access (SD-Access):
- Simplified operations and deployment with policy-based automation from edge to cloud managed with Cisco Identity Services Engine (ISE)
- Network assurance and improved resolution time through Cisco DNA Center™
- Plug and Play (PnP) enabled: A simple, secure, unified, and integrated offering to ease new branch or campus device rollouts or updates to an existing network
- Cisco IOS XE: A Common Licensing based operating system for the enterprise Cisco Catalyst 9000 product family with support for model-driven programmability and streaming telemetry

• ASIC with programmable pipeline and micro-engine capabilities, along with template-based, configurable allocation of Layer 2 and Layer 3 forwarding, Access Control Lists (ACLs), and Quality of Service (QoS) entries

#### **Supported Products**

Table 2 shows the recommended supported products.

| Network modules                               |   |  |
|---|---|--|
| Product number                                | Product description   |  |
| C9200-NM-4X                                   | Catalyst 9200 4 x 10GE Network Module   |  |
| StackWise-80 and StackWise-160 Kit and cables |   |  |
| Product number                                | Product description   |  |
| C9200-STACK-KIT=                              | C9200 Stack Kit Spare   |  |
| C9200L-STACK-KIT=                             | C9200L Stack Kit Spare  |  |
| STACK-T4-50CM                                 | 50CM Type 3 Stacking Cable  |  |
| STACK-T4-1M                                   | 1M Type 3 Stacking Cable  |  |
| STACK-T4-3M                                   | 3M Type 3 Stacking Cable  |  |
| Soft Licenses                                 |   |  |
| Product number                                | Product description   |  |
| C9200L-DNA-P-24                               | C9200L DNA Premier Term, 24-Port: Includes Term Licenses for DNA Advantage, 25 ISE Base & 25 ISE Plus Endpoints, 25 Stealthwatch Flows (including Virtual Flow Collector & Management Console). Requires separate purchase of ISE appliance/ISE VM and DNA Center appliance |  |
| C9200L-DNA-P-24-3Y                            | C9200L DNA Premier, 24-port, 3Y Term - DNA, 25 ISE PLS and ISE BASE, 25 SWATCH  |  |
| C9200L-DNA-P-24-5Y                            | C9200L DNA Premier, 24-port, 5Y Term - DNA, 25 ISE PLS and ISE BASE, 25 SWATCH  |  |
| C9200L-DNA-P-24-7Y                            | C9200L DNA Premier, 24-port, 7Y Term - DNA, 25 ISE PLS and ISE BASE, 25 SWATCH  |  |
| Power supplies                                |   |  |
| Product Number                                | Product Description   |  |
| PWR-C5-600WAC/2=                              | 125WAC power supply spare   |  |

## **Compare to Similar Items**

Table 3 shows the comparison.

| Product number  | Product description   |
|-----------------|---|
| C9200L-24T-4X-A | Catalyst 9200L 24-port Data 4x10G uplink Switch, Network Advantage  |
| C9200L-24T-4X-E | Catalyst 9200L 24-port Data 4x10G uplink Switch, Network Essentials |
| C9200L-24P-4X-A | Catalyst 9200L 24-port PoE+ 4x10G uplink Switch, Network Advantage  |
| C9200L-24P-4X-E | Catalyst 9200L 24-port PoE+ 4x10G uplink Switch, Network Essentials |

### **Get More Information**

Do you have any question about the C9200L-24P-4X-E?

Contact us now via **Live Chat** or **sales@router-switch.com**.

# Specification

| C9200L-24P-4X-E Specification                         |   |  |
|---|---|--|
| Downlinks total 10/100/1000 or PoE+ copper ports      | 24 ports full PoE+                                      |  |
| Uplink configuration                                  | 4x 10G fixed uplinks                                    |  |
| Default primary AC power supply                       | PWR-C5-600WAC   |  |
| Fans  | Fixed redundant   |  |
| Software  | Network Essentials                                      |  |
| Chassis Dimensions                                    | 1.73 x 17.5 x 11.3 in<br>4.4 x 44.5 x 28.8 cm           |  |
| Virtual Networks                                      | 1   |  |
| Stacking bandwidth                                    | 80 Gbps   |  |
| Total number of MAC addresses                         | 16,000  |  |
| Total number of IPv4 routes (ARP plus learned routes) | 11,000 (8,000 direct routes and 3,000 indirect routes)  |  |
| IPv4 routing entries                                  | 3,000   |  |
| IPv6 routing entries                                  | 1,500   |  |
| Multicast routing scale                               | 1,000   |  |
| QoS scale entries                                     | 1,000   |  |
| ACL scale entries                                     | 1,500   |  |
| Packet buffer per SKU                                 | 6 MB buffers for 24- or 48-port Gigabit Ethernet models |  |
| Flexible NetFlow (FNF) entries                        | 16,000 flows on 24- and 48-port Gigabit Ethernet models |  |
| DRAM  | 2 GB  |  |
| Flash   | 4 GB  |  |
| VLAN IDs  | 1024  |  |
| Total Switched Virtual Interfaces (SVIs)              | 512   |  |
| Jumbo frames  | 9198 bytes  |  |
| Wireless bandwidth per switch                         | N/A   |  |
| Switching capacity                                    | 128 Gbps  |  |
| Forwarding rate                                       | 190.4 Mpps  |  |
| Mean time between failures (hours)                    | 390,310   |  |

# Download Resource

## **Support and Resources**



**Cisco Catalyst 9200 Switch Datasheet** 

# Contact Us

## Want to buy this series of products? please contact us:

● Tel: +1-626-239-8066 (USA) +852-3050-1066 / +852-3174-6166

Fax: +852-3050-1066 (Hong Kong)Email: sales@router-switch.com

## **Order Now**

GO to buy this product: https://www.router-switch.com/c9200I-24p-4x-e.html