



8-Port Gigabit Desktop/Rackmount Switch with 8-Port PoE+

MODEL: TL-SG1008MP Datasheet



Overview

The TL-SG1008MP is an 8-port Gigabit Desktop/Rackmount Switch with all 8 ports supporting the PoE+ standard. It provides a simple way to expand a wired network by transferring power and data over a single Ethernet Cable. With a total power budget of 126 W, up to 30 W per port, TL-SG1008MP can power more high-powered devices such as wireless Access Points (APs), IP Cameras or IP Phones. Moreover, with innovative energy-efficient technology, the TL-SG1008MP can save power consumption, making it an eco-friendly solution for your business network.

Power over Ethernet for Simplified Network Deployment

- Features eight 802.3af/at compliant PoE+ ports, with a total PoE power budget of 126 W
- Flexible deployment for PoE supported devices such as wireless access points (APs), IP cameras and IP phones
- Designed to use a single Ethernet cable for both data and power transmission, lowering infrastructure costs

Gigabit Expansion Solution

- Eight 10/100/1000 Mbps ports provide up to 16 Gbps Switching Capacity.
- 16 KB Jumbo Frame improves performance of large data transfer.
- IEEE 802.3x flow control provides reliable data transfer.

Highlight Performance

- 802.1p and DSCP QoS ensure smooth traffic.
- IGMP Snooping optimizes multicast applications.

Easy to Use

- Just plug & play, no configuration required
- Auto MDI/MDIX eliminates the need for crossover cables.
- Auto-negotiation intelligently adjusts for compatibility and optimal performance.

Specifications

Hardware Features & Performance

Product Picture	
Model	TL-SG1008MP
Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3x, IEEE 802.3af, IEEE 802.3at, IEEE 802.1p
Network Ports	8*10/100/1000 Mbps RJ45 ports with 8 PoE ports
Network Media (Cable)	10Base-T: UTP category 3, 4, 5 cable (maximum 100 m) EIA/TIA-568 100_STP (maximum 100 m) 100Base-TX: UTP category 5, 5e or above cable (maximum 100 m) EIA/TIA-568 100_STP (maximum 100 m) 1000Base-T: UTP category 5, 5e cable or above cable (maximum 100 m) EIA/TIA-568 100_STP (maximum 100 m)
Auto Negotiation	YES
Auto MDI/MDIX	YES
Forwarding Mode	Store and Forward
Switch Capacity	16 Gbps
MAC Address Table	4K, Auto-learning, Auto-aging
Flow Control	YES
Backpressure	YES
Fan Quantity	1
Max Power Consumption	9.89 W (220 V/50 Hz. no PD connected) 144.36 W (110 V/60 Hz. with 126 W PD connected)
Max Heat Dissipation	33.74 BTU/h (no PD connected) 492.56 BTU/h (with 126 W PD connected)
LED	Power, 1000 Mbps, Link/Act, PoE Status, PoE MAX
Dimensions	11.6 × 7.1 × 1.7 in. (294 × 180 × 44 mm)
Certification	CE, FCC
Operating Temperature	0 °C to 40 °C (32 °F to 104 °F)
Storage Temperature	-40 °C to 70 °C (-40 °F to 158 °F)
Operating Humidity	10% to 90% non-condensing
Storage Humidity	5% to 90% non-condensing
Jumbo Frame	16 KB

Ordering Information

Host Switches	
Product Model	Description
TL-SG1008MP	8-Port Gigabit Desktop/Rackmount Switch with 8-Port PoE
TL-SG1008P	8-Port Gigabit Desktop Switch with 4-Port PoE
PoE Adapter	
Product Model	Description
TL-POE10R	PoE Splitter
Router	
Product Model	Description
TL-ER604W	SafeStream Wireless N Gigabit Broadband VPN Router
TL-ER6120	SafeStream Gigabit Dual-WAN VPN Router

www.tp-link.com

Specifications are subject to change without notice. TP-Link is a registered trademark of TP-Link Technologies Co., Ltd. Other brands and product names are trademarks or registered trademarks of their respective holders. Copyright © 2019 TP-Link Technologies Co., Ltd. All rights reserved.