

commBOX Interactive Classic Specs

Models



Classic 55

CBIC55



Classic 65

CBIC65



Classic 75

CBIC75



Classic 86

CBIC86



Classic 98

CBIC98

Screen

Resolution

UD 3840x2160 @60Hz

Brightness

450cd / m2

Viewing Angle

178°

Noise

Below 40dB 25C

Surface Temp

Below 10 at 24C

Operating Con

5C to 35C

Power Req

AC 100 to 240V, 50/60Hz Power Supply

Power Max

130W

260W

470W

470W

520W

Power Average

110W

240W

430W

430W

480W

Touch Points

4 / 10 Fingertips or any tips

4 /10 Fingertips or any tips

Touch Technology

Optical

Optical

LED Display

LG Commercial Grade

LG Commercial Grade

VESA

456x400




456x400

400x600

400x606

400x744

Dimensions



Screen

1413(W) x 838(H)
x 102(D)mm

1638(W) x 960(H)
x 108(D)mm

1840(W) x 1085(H)
x 128(D)mm

2093(W) x 1234(H)
x 125(D)mm

2368(W) x 1393(H)
x 141(D)mm

Packed

1590(W) x 960(H)
x 270(D)mm

1850(W) x 1100(H)
x 320(D)mm

2050(W) x 1225(H)
x 350(D)mm

2275(W) x 1360(H)
x 400(D)mm

2600(W) x 1550(H)
x 560(D)mm

Weight

Screen

50kg

68kg

98kg

122kg

134kg

Packed

57kg

81kg

116kg

147kg

154kg

Accessories

HDMI Cable, USB Cable, Stylus Pen, Cleaning Cloth

HDMI Cable, USB Cable, Stylus Pen, Cleaning Cloth

Speakers

15W x 2 Internal Speakers

15W x 2 Speaker Out



15W x 2 Internal Speakers

15W x 2 Speaker Out



Input/Output

Input: VGA + 3.5 Stereo Audio, Component, 4 X HDMI,
USB A for content, USB B for Touch, RS232
Output: Speaker 2 x 3.5 Mono, SPDIF, Line level output

Input: VGA + 3.5 Stereo Audio, Component, 4 X HDMI,
USB A for content, USB B for Touch, RS232
Output: Speaker 2 x 3.5 Mono, SPDIF, Line level output