



Overview

Lead time	Usually in Stock
-----------	------------------

General

Provided equipment	Documentation CD Rack mounting hardware Rack mounting support rails USB cable
--------------------	--

Physical

Cable length	2.00 m
Number of rack unit	2U
Depth	68.3 cm
Height	8.6 cm
Net weight	44.28 kg
Width	43.2 cm

Input

Network frequency	50/60 Hz +/- 3 Hz auto-sensing
Plug standard	BS1363A British IEC 320 C20 Schuko CEE 7 / EU1-16P
Input voltage limits	151...302 V adjustable 160...286 V
Inputvolt_other	220 V 240 V
Input voltage	230 V

Output

Rated power in W	2700 W
Maximum configurable power in W	2700 W
Harmonic distortion	Less than 5 %
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Outputvoltage_other	220 V 240 V
UPS type	Line interactive
Wave type	Sine wave
Nb of power socket outlets	8 IEC 320 C13 3 IEC Jumpers 1 IEC 320 C19
Output voltage	230 V

Conformance

Product certifications	CE EAC IRAM RCM VDE WEEE
Standards	EN 60950 EN/IEC 62040-1 EN/IEC 62040-2
Marking	GS Mark

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage altitude	0.00...15240.00 m
Acoustic level	55 dBA
Heat dissipation	348 Btu/h

Batteries & Runtime

Battery type	Lead-acid battery
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 h
Number of battery replacement quantity	1
Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Liquid value	0

Communications & Management

Free slots	1
Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

Surge Protection and Filtering

Surge energy rate	320 J
-------------------	-------

Packing Units

Package 1 Weight	51.7 kg
Package 1 Height	25.4 cm
Package 1 width	60 cm
Package 1 Length	98 cm
Number of Units in Package 3	8

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Optimized Energy Efficiency	Energy efficient product

Contractual warranty

Warranty	3 years repair or replace (excluding battery) and 2 years for battery
----------	---