



Overview

Lead time	Usually in Stock
-----------	------------------

General

Provided equipment	User manual Rack mounting brackets Rack mounting support rails CD with software
--------------------	--

Physical

Number of rack unit	8U
Colour	Black
Depth	73 cm
Height	35.6 cm
Net weight	104.09 kg
Width	48.3 cm

Input

Network frequency	50/60 Hz +/- 5 Hz auto-sensing
Number of input connectors	1 hard wire 3-wire
Input voltage limits	155...276 V
Input voltage	230 V

Output

Rated power in W	2800 W
Maximum configurable power in W	4200 W
Harmonic distortion	Less than 5 % at full load
Output frequency	47...53 Hz for 50 Hz nominal sync to mains 50 Hz +/- 0.1 % for 50 Hz nominal unsynchronised
Crest factor	Up to 5 : 1
UPS type	Double conversion online
Wave type	Sine wave
Nb of power socket outlets	8 IEC 60320 C13

Bypass type	Internal bypass (automatic and manual)
Output voltage	230 V

Conformance

Product certifications	C-Tick CE IRAM VDE
Standards	EN 50091-2 EN 60950

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage altitude	0.00...15240.00 m
Acoustic level	60 dBA
Heat dissipation	1181 Btu/h

Batteries & Runtime

Battery type	Lead-acid battery
Number of battery filled slots	2
Number of battery free slots	2
Battery recharge time	4 h
Additional information	UPS accepts 1-2 additional battery packs Configurable for 220 : 230 or 240 nominal output voltage
Liquid value	0

Communications & Management

Free slots	1
Preinstalled device	Network management card 2 with environmental monitoring
Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
Emergency power off	Yes

Packing Units

Package 1 Weight	116.36 kg
Package 1 Height	50.8 cm
Package 1 width	58.4 cm
Package 1 Length	78.7 cm

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	2 years repair or replace, optional on-site warranties available, optional extended warranties available
----------	--