

## APC Easy UPS On-Line SRV RM Extended Runtime 6000VA 230V No Battery

### SRVPM6KRIL

Call for More Information 800-800-4272



- High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions
- Includes: CD with software, USB cable, User Manual

#### Output

Output power capacity	6.0kWatts / 6.0kVA
Max Configurable Power (Watts)	6.0kWatts / 6.0kVA
Nominal Output Voltage	230V
Other Output Voltages	220, 240
Load Crest Factor	3 : 1
Topology	Double Conversion Online
Waveform type	Sine wave

#### Input

Nominal Input Voltage	230V
Input frequency	40 - 70 Hz
Input Connections	Hard Wire 3-wire
Other Input Voltages	220, 240

#### Batteries & Runtime

Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	3hour(s)

#### Communications & Management

Control panel	Multi-function LCD status and control console
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Emergency Power Off (EPO)	Yes

**Disclaimer:** Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

## Technical Specifications

### Surge Protection and Filtering

Surge energy rating	600Joules
---------------------	-----------

### Physical

Maximum Height	3.43inches (87MM, 8.7CM)
Maximum Width	17.24inches (438MM, 43.8CM)
Maximum Depth	24.21inches (615MM, 61.5CM)
Net Weight	30.86lbs. (14.0KG)
Shipping weight	39.68lbs. (18.0KG)
Shipping Height	9.45inches (240MM, 24.0CM)
Shipping Width	23.62inches (600MM, 60.0CM)
Shipping Depth	29.92inches (760MM, 76.0CM)

### Environmental

Operating Temperature	32 - 104 °F (0 - 40 °C)
Operating Relative Humidity	0 - 95 (non-condensing) %
Operating Elevation	0-10000ft (0-3000meters)
Storage Relative Humidity	0 - 95 (non-condensing) %
Storage Elevation	0-49212ft (0-14763.6meters)

### Conformance

Approvals	CE, IEC 62040-1-1, IEC 62040-1-2
Standard warranty	2 years repair or replace

### Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs

**Disclaimer:** Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.