



Overview

| | |
|-----------|------------------------------|
| Lead time | Usually Ships within 2 Weeks |
|-----------|------------------------------|

General

| | |
|--------------------|---|
| Provided equipment | <ul style="list-style-type: none"> CD with software Documentation CD Installation guide Rack mounting support rails Removable support feet Smart UPS signalling RS-232 cable USB cable |
|--------------------|---|

Physical

| | |
|---------------------|----------|
| Cable length | 1.83 m |
| Number of rack unit | 2U |
| Colour | Black |
| Depth | 49 cm |
| Height | 8.9 cm |
| Net weight | 24.82 kg |
| Width | 43.2 cm |

Input

| | |
|----------------------------|---------------------------------------|
| Network frequency | 50/60 Hz +/- 3 Hz auto-sensing |
| Plug standard | IEC 320 C14 |
| Input voltage limits | 151...302 V adjustable 160...286 V |
| Switching current capacity | 10 A |
| Input voltage | 230 V |

Output

| | |
|---------------------------------|---------------------------------|
| Rated power in W | 1200 W |
| Maximum configurable power in W | 1200 W |
| Harmonic distortion | Less than 5 % |
| Output frequency | 50/60 Hz +/- 3 Hz sync to mains |
| UPS type | Line interactive |
| Wave type | Sine wave |
| Nb of power socket outlets | 8 IEC 320 C13 2 IEC Jumpers |
| Output voltage | 230 V |

Conformance

| | |
|------------------------|----------------------------|
| Product certifications | C-Tick CE VDE EAC |
| Standards | EN 50091-1 EN 50091-2 |

Environmental

| | |
|---------------------------------------|-------------------|
| Ambient air temperature for operation | 0...45 °C |
| Relative humidity | 0...95 % |
| Operating altitude | 0...10000 ft |
| Ambient air temperature for storage | -15...45 °C |
| Storage altitude | 0.00...15240.00 m |
| Acoustic level | 40 dBA |
| Heat dissipation | 133 Btu/h |

Batteries & Runtime

| | |
|--|-------------------|
| Battery type | Lead-acid battery |
| Number of battery filled slots | 0 |
| Number of battery free slots | 0 |
| Battery recharge time | 3 h |
| Number of battery replacement quantity | 1 |
| Liquid value | 0 |

Communications & Management

| | |
|---------------------|--|
| Free slots | 0 |
| Preinstalled device | Network management card 2 with environmental monitoring |
| Control panel | Multifunction LCD status and control console |
| Alarm | Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm |
| Emergency power off | Yes |

Surge Protection and Filtering

| | |
|-------------------|--|
| Surge energy rate | 645 J |
| Noise suppression | Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449 |

Packing Units

| | |
|------------------|---------|
| Package 1 Weight | 30 kg |
| Package 1 Height | 24.6 cm |

| | |
|------------------------------|---------|
| Package 1 width | 58.9 cm |
| Package 1 Length | 62 cm |
| Number of Units in Package 3 | 8 |

Offer Sustainability

| | |
|-----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Optimized Energy Efficiency | Energy efficient product |

Contractual warranty

| | |
|----------|---|
| Warranty | 3 years repair or replace (excluding battery) and 2 years for battery |
|----------|---|