



Overview

Lead time	Usually in Stock
-----------	------------------

General

Provided equipment	Installation guide Rack mounting support rails USB cable
--------------------	--

Physical

Number of rack unit	1U
Colour	Black with silver front bezel
Depth	23.2 cm
Height	4.4 cm
Net weight	4.06 kg
Width	43.2 cm

Input

Network frequency	47...63 Hz
Plug standard	IEC 60320 C14
Input voltage limits	208...253 V
Input voltage	230 V

Output

Rated power in W	400 W
Maximum configurable power in W	400 W
Wave type	Sine wave
Nb of power socket outlets	4 IEC 60320 C13

Output voltage	230 V
----------------	-------

Conformance

Product certifications	C-Tick CE EAC RCM
Standards	IEC 60950 IEC 62040-1-1 IEC 62040-1-2
Marking	GS Mark
Equipment protection policy	Lifetime : \$150000

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	10...90 % non-condensing
Operating altitude	0...6561 ft
Ambient air temperature for storage	-10...40 °C
Storage altitude	0.00...14999.82 m
Acoustic level	45 dBA

Batteries & Runtime

Battery type	Li-Ion (Lithium-Ion)
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 h
Liquid value	0

Communications & Management

Free slots	0
Control panel	LED status display with on line : on battery : replace battery and building wiring fault
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

Surge Protection and Filtering

Surge energy rate	510 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Package 1 Weight	6 kg
Package 1 Height	16.8 cm
Package 1 width	59 cm
Package 1 Length	33.7 cm

Contractual warranty

Warranty	5 year repair or replace
----------	--------------------------