



TL-D400S	
Drive Bay	4 x 3.5-inch SATA 6Gb/s, 3Gb/s
Drive Compatibility	3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
Audio Alert On/Off Switch	Yes
Form Factor	Tower
Host Interface	1 x SFF-8088
LED Indicators	HDD 1-4, Status, Link, Fan error
Buttons	Power switch
Dimensions (HxWxD)	168.5 × 160.2 × 219 mm
Weight (Net)	3.66 kg
Max. number of HDDs/SSDs supported	4
Hard Drive Type	3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
Operating temperature	0 - 40 °C (32°F - 104°F)
Relative Humidity	5-95% RH non-condensing, wet bulb: 27°C (80.6°F)
Power Supply Unit	65W adapter, 100 - 240V
Power Consumption: Operating Mode, Typical	22.985 W
Fan Mode Switch	Yes (Auto, high, medium, low)
Fan	1 x 120mm, 12VDC
Sound Level	20.1 db(A)
System Warning	Buzzer
Kensington Security Slot	Yes

Natar Has anly ONAD mamon, modulas to maintain austam norformanes and stability. Ear NAC davises with mare than one mamon

Note. Ose only QNAP memory modules to maintain system performance and stability. For INAS devices with more than one memory slot, use QNAP modules with identical specifications. Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

* Sound Level Test Environment: Refer to ISO 7779; Maximum HDD loaded; Bystander Position; Average data from 1 meter in front of operating NAS.

Designs and specifications are subject to change without notice.