

Spec Sheet

2 Port Dual DVI USB KVM Switch with Audio & USB 2.0 Hub

StarTech ID: SV231DD2DUA



The SV231DD2DUA 2-port Dual DVI USB KVM Switch allows two PCs, each with dual DVI video outputs, to share two monitors, one microphone and set of speakers, one keyboard and one mouse as well as two other USB peripherals.

An ideal solution for graphic designers, CAD/CAM designers or educational and financial institutions, the dual view KVM Switch allows you to instantly switch back and forth between dual DVI display PCs at the touch of a button, while maintaining professional level video quality on both monitors. The dual DVI switch also features an integrated USB hub port that allows USB 2.0 peripherals such as thumb drives, external hard drives or web cams to be shared between attached systems - eliminating duplicate peripheral costs.

Please Note: This KVM switch supports DVI-D (digital) signaling only and it is recommended wherever possible to use DVI-D cabling across all PC to KVM and KVM to Console connections to ensure proper function. Please contact technical support if you require assistance identifying the proper cables.

Backed by a StarTech.com 3 year warranty and free lifetime technical support.

Applications

- Dual system control for single user workstations with dual head video cards, increasing user productivity in the office
- Control two dual display multimedia computers with a single set of console peripherals (Keyboard, Mouse, and two Monitors)
- Ideal for financial/banking industries, graphic designers, multi-media applications and industries using CAD/CAM applications, and multiple screens
- Integrated USB 2.0 hub and Mic/Audio ports allow the user to have full multimedia control of two computers and share USB peripherals



Spec Sheet

Features

- Front panel push-buttons and Hot-key functions for easy switching
- Supports resolutions up to 1920x1200 (DVI-Digital)
- USB 2.0 hub for peripheral sharing (Thumb drives, external hard drives, web cams, etc.)
- Audible tone confirms port switching
- Combined or independent switching of audio ports
- EDID retention eliminates hassle when switching between computers as the KVM "remembers" monitor settings
- Supports all USB-capable operating systems (Windows 98e/SE/ME/2000/XP/Vista/7, Linux, Mac OS, etc.)
- Rugged, all-metal chassis for use in harsh environments
- TMDS compliant to support DDC2B emulation and HDCP for digital contents protection
- Status LED display for easy port status monitoring

www.startech.com
1 800 265 1844



Hard-to-find made easy®

Technical Specifications

Warranty 3 Years Audio Yes KVM Ports 2 PC Interface USB PC Video DVI Type Multi-Monitor Yes Rack-No Mountable Cables No Included Daisy-Chain No Console 2 - 3.5 mm Mini-Jack (3 Position) Female Interface(s) Console 2 - DVI-I (29 pin) Female Interface(s) Console 4 - USB A (4 pin) Female Interface(s) Host 2 - USB B (4 pin) Female Connectors 4 - 3.5 mm Mini-Jack (3 Position) Female Host Connectors Host 4 - DVI-I (29 pin) Female Connectors DVI Support Yes - Single Link IP Control No 1920 x 1200 Maximum Digital Resolutions Maximum 1 Number of Users Port Push Button and Hotkeys Selection Support OS OS independent; No software or drivers required Compatibility

Spec Sheet



Hard-to-find made easy*

Spec Sheet

| Note | This KVM switch supports DVI-D (digital) signaling only and it is recommended wherever possible to use DVI-D cabling across all PC to KVM and KVM to Console connections to ensure proper function. Please contact technical support if you require assistance identifying the proper cables. |
|---------------------------------|---|
| Color | Black |
| Enclosure Type | Steel |
| Product Length | 6.4 in [163 mm] |
| Product Width | 6.3 in [160 mm] |
| Product Height | 2.2 in [57 mm] |
| Product Depth | 3.9 in [100 mm] |
| Product Weight | 26.5 oz [750 g] |
| LED Indicators | 1 - Green - Power |
| LED Indicators | 4 - Green - Host Online, Red - Host Selected |
| Input Voltage | 110 ~ 240 AC |
| Input Current | 0.8A |
| Output Voltage | 12 DC |
| Output Current | 1.5A |
| Center Tip Polarity | Positive |
| Plug Type | M |
| Operating Temperature | 0°C to 40°C (32°F to 104°F) |
| Storage Temperature | -20°C to 60°C (-4°F to 140°F) |
| Humidity | 90% RH |
| Shipping (Package) Weight | 2.6 lb [1.2 kg] |
| lncluded in Package | 1 - Two Port Dual DVI KVM |

www.startech.com 1 800 265 1844



Hard-to-find made easy®

Included in 1 - Rubber Feet Package Included in 1 - Universal Power Adapter (US/UK/EU) Package Included in 1 - Manual Package

Certifications, Reports and Compatibility

C€ F©







www.startech.com 1 800 265 1844