



Overview

Lead time	Usually in Stock
-----------	------------------

General

Provided equipment	Installation guide Locking input power cord Rack mounting brackets Safety guide
--------------------	--

Physical

Cable length	3.00 m
Colour	Black
Depth	4.6 cm
Height	179.4 cm
Net weight	5.61 kg
Width	5.5 cm

Input

Permissible voltage	220...240 V
Max line current	16 A
Communication port protocol	SNMP Redfish
Input current limits	16 A
Load capacity	3700 VA
Network frequency	50/60 Hz
Plug standard	IEC 60309 16 A 2P + E
Input voltage	230 V

Output

Number of power socket outlets	21 IEC 60320 C13 3 IEC 60320 C19
--------------------------------	-------------------------------------

Conformance

Product certifications	FCC part 15 class A VDE RCM EAC
Standards	EN 55022 class A EN 55024 EN 61000-3-2 EN 61000-3-3 ICES-003

Environmental

Ambient air temperature for operation	-5...45 °C
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0.00...15240.00 m

Batteries & Runtime

Communication network type	10/100/1000BASE-T Wi-Fi (optional)
----------------------------	---------------------------------------

Packing Units

Package 1 Weight	8.59 kg
Package 1 Height	200.2 cm
Package 1 width	16.5 cm
Package 1 Length	11.4 cm
Number of Units in Package 3	48

Contractual warranty

Warranty	3 years repair or replace
----------	---------------------------