

## PC42t

### 4" Desktop Printer

Based on more than 40 years of bar code printing innovations, the PC42t desktop printer sets new standards for user-friendliness and affordability. Exceptionally compact and easy to use, this printer is simple to install and is ready to print quickly. Quiet, reliable operation and intuitive design make the PC42t the right fit for light-duty labeling applications in a variety of industries.

Available in either 12.7 mm (½ in) or 25.4 mm (1 in) ribbon core configurations, the PC42t supports media as wide as 110 mm (4.3 in) and fits right into existing printing environments. The 25.4 mm configuration is compatible with ribbon lengths up to 300 m (984 ft) — more than four times the length of competitive offerings. With support for longer ribbons, downtime is reduced and ribbons can be shared with larger printers to provide increased media flexibility.

The PC42t includes broad, industry standard connectivity. Up to four ports are built-in: standard USB device and USB host, plus serial or serial+Ethernet. With a user-installable USB-to-parallel cable, the PC42t easily drops into virtually any environment.

With its compact size, common media specifications, and support for ZPL-II and EPL emulation, along with Honeywell's popular Direct Protocol (DP), the PC42t provides an easy upgrade path from a variety of legacy Intermec and competitive printers.

With its affordable price and modern features, the PC42t represents a smart solution for the small or medium business looking to improve productivity in label making operations.



*Easy to install and ready to print quickly, the streamlined PC42t is an economical choice for media up to 110 mm (4.3 in) wide.*

Economical to purchase and use, the PC42t is also a great choice for those looking to deploy thermal label printing for the first time, or for those transitioning away from more expensive inkjet- or laser-based label printing methods.

## FEATURES



An economical solution for light-duty thermal printing applications.



Supports a wide range of media, including 12.7 mm (½ in) or 25.4 mm (1 in) ribbon cores (depending on the model).



Industry-standard connectivity includes USB host and device, Ethernet, parallel and serial communications.



Easy to use, with a quick-opening design for media replenishment.



Supports ESim (EPL), ZSim (ZPL-II) and Direct Protocol (DP) print languages for maximum compatibility.

# PC42t Technical Specifications

## PHYSICAL

**Dimensions (LxWxH):** 297 mm x 226 mm x 177 mm (11.7 in x 8.9 in x 7.0 in)  
**Weight:** 2.5 kg (5.5 lbs)

## MEDIA

**Max. Media Diameter:** 127.0 mm (5.0 in)  
**Media Core Sizes:** 25.4 mm (1.0 in), 38.1 mm (1.5 in)  
**Media Width:** 25.4 mm (1.0 in) to 110 mm (4.3 in)  
**Min. Label Length:** 9.6 mm (0.3 in)

## RIBBON

**Ribbon Support:** Coated Side Out  
**Max. Ribbon Diameter:** 68.0 mm (2.7 in)  
**Ribbon Core Sizes:** 12.7 mm (0.5 in), 25.4 mm (1.0 in)  
**Ribbon Width:** 25.4 mm (1.0 in) to 109.2 mm (4.3 in)  
**Max. Ribbon Length:** 25.4 mm (1.0 in) core: 300.0 m (984.0 ft), 12.7 mm (0.5 in) core: 75.0 m (246.0 ft)

## PRINTING

**Print Resolution:** 8.0 dpmm (203 dpi)  
**Max. Print Speed:** 101.6 mm/s (4.0 ips)  
**Max. Print Width:** 104.1 mm (4.1 in)

## COMMUNICATIONS

**Standard Interfaces:** USB Device, USB Host with Serial or Ethernet (depending on model)  
**Options – User Installable:** Parallel adapter cable  
**Protocols:** *Network:* TCP/IP-suite (TCP, UDP, ICMP, IGMP), DHCP, BOOTP, LPR, FTP, web page and Telnet 9100, IPv4 *Serial Flow Control:* XON/XOFF, RTS/CTS

## USER INTERFACE

**Display:** 1 Feed Button and LED Display  
**Web Page Languages:** English and Simplified Chinese (Default), Spanish, Portuguese, Russian, Korean, Japanese, Thai

## GRAPHICS & BAR CODES

**Native Graphic Formats:** 1-bit BMP, GIF, PCX, PNG  
**Barcode Symbolologies:** All major 1D and 2D symbolologies are supported, including Aztec, Code 16K, Code 49, Data Matrix, Dot Code, EAN-8, EAN-13, EAN, UCC 128, Grid Matrix, HIBC 39, HIBC 128, MaxiCode, MSI (modified Plessey), PDF417, Micro PDF417, Planet, Plessey, Postnet, QR-Code, RSS-14 (variations)

## SOFTWARE

**Printer Command Languages:** Direct Protocol (DP), ZSim (ZPL-II), ESim (EPL)  
**Drivers:** BarTender®, InterDriver Windows® Printer Driver  
**Character Sets:** English & Extended Latin, Arabic, Baltic & Baltic Rim, Cyrillic, Greek, Hebrew, Thai, Turkish, Vietnamese, & more with Monotype™ Universal Font Scaling Technology (UFST) & WorldType Layout Engine (WTLE)

## ENVIRONMENTAL

**Operating Temperature:** +5°C to +40°C (+41°F to +104°F) 10 to 80% RH non-condensing  
**Storage Temperature:** -40°C to +60°C (-40°F to +140°F) @ 10 to 90% RH

## ELECTRICAL

**Input:** 100-240V AC @ 50-60 Hz, 1.5 A  
**Output:** 24V DC, 2.5 A

## MEMORY

**Standard:** 64 MB Flash, 64 MB SDRAM  
**Optional:** Up to 32 GB (via user-supplied USB thumb drive) formatted as FAT16 or FAT32

## OPTIONS

**Factory Installable:** Ethernet, serial port

## APPROVALS

**Regulatory:** UL, cUL, cULus, CE, FCC Class A, D Mark CCC, KCC, RCM  
**Safety:** *North America:* UL & cUL Listed, UL 60950-1 *Europe:* D Mark, EN 60950-1; *CE Mexico:* NYCE Certified, NOM 19 *Other Countries:* IEC 60950-1  
**EMC:** USA FCC Title 47, Part 15, Subpart A, Class A; Europe EMC Directive (EN55022 Class A + EN55024); CISPR22

## WARRANTY

One Year Standard Warranty; Additional Honeywell Repair Services Packages Available

For more Information, visit [www.barcodes.com.au/PC42t](http://www.barcodes.com.au/PC42t)  
or call us on 1300 800 999

## Honeywell Scanning & Mobility

9680 Old Bailes Road  
Fort Mill, SC 29707  
800-582-4263  
[www.honeywell.com](http://www.honeywell.com)



Phone: 1300 800 999  
Email: [sales@barcodes.com.au](mailto:sales@barcodes.com.au)  
Website: [www.barcodes.com.au](http://www.barcodes.com.au)

PC42t-DS-APAC Rev A 07/15  
© 2015 Honeywell International Inc.

**Honeywell**