# Product data sheet
## Characteristics

# SRV2KI-AR
## APC Easy UPS SRV 2000VA 230V



## Overview

| | |
|---|---|
| Lead time | Usually in Stock |

## General

| | |
|---|---|
| Provided equipment | Basic UPS signalling RS-232 cable<br>CD with software<br>User manual<br>USB cable |

## Physical

| | |
|---|---|
| Cable length | 1.50 m |
| Colour | Black |
| Depth | 28.8 cm |
| Height | 22.3 cm |
| Net weight | 9.3 kg |
| Width | 14.5 cm |

## Input

| | |
|---|---|
| Network frequency | 40...70 Hz |
| Plug standard | IEC 60320 C14 |
| Input voltage limits | 110...285 V adjustable (half load)<br>160...280 V |
| Inputvolt_other | 220 V<br>240 V |
| Input voltage | 230 V |

## Output

| | |
|---|---|
| Rated power in W | 1600 W |
| Maximum configurable power in W | 1600 W |
| Output frequency | 50/60 Hz +/- 3 Hz sync to mains |
| Outputvolt_other | 220 V<br>240 V |
| Crest factor | 3 : 1 |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---|---|
| UPS type | Double conversion online |
| Wave type | Sine wave |
| Nb of power socket outlets | 3 Argentinean |
| Bypass type | Internal bypass (automatic and manual) |
| Output voltage | 230 V<br>240 V |

## Conformance

| | |
|---|---|
| Product certifications | CE<br>IRAM |

## Environmental

| | |
|---|---|
| Ambient air temperature for operation | 0…40 °C |
| Relative humidity | 0…95 % non-condensing |
| Operating altitude | 0...10000 ft |
| Ambient air temperature for storage | -20…50 °C |
| Storage altitude | 0.00…15240.00 m |
| Acoustic level | 50 dBA |
| IP degree of protection | IP20 |

## Batteries & Runtime

| | |
|---|---|
| Battery type | Lead-acid battery |
| Number of battery filled slots | 0 |
| Number of battery free slots | 0 |
| Battery recharge time | 4 h |
| Additional information | Configurable for 220 : 230 or 240 nominal output voltage |
| Liquid value | 0 |

## Communications & Management

| | |
|---|---|
| Free slots | 1 |
| Control panel | Multifunction LCD status and control console |
| Alarm | Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm |

## Surge Protection and Filtering

| | |
|---|---|
| Surge energy rate | 600 J |

## Packing Units

| | |
|---|---|
| Package 1 Weight | 10.6 kg |
| Package 1 Height | 33 cm |
| Package 1 width | 23.5 cm |
| Package 1 Length | 36.5 cm |
| SCC14 | 10731304340215 |

## Contractual warranty

| | |
|---|---|
| Warranty | 2 years repair or replace |